

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



SMART DESIGNS COME FROM SMART SOLUTIONS.



NESTAFLEX
FLEXIBLE CONVEYORS

376 

GRAVITY SKATE WHEEL CONVEYOR

AL – Adjustable leg heights &
FL – Fixed leg heights for added durability



The **376** is a heavy duty, gravity conveyor that features **DOUBLE** welded cross braces, heavy duty square tubing legs and reinforced inner legs for added support. The **ALL STEEL** reinforced leg and frame design provides the strength necessary to handle heavy cartons in an industrial environment. The all bolted design uses shoulder bolts, steel lock nuts and is additionally secured with industrial thread lock to help reduce maintenance. The **FOUR POINT** leg connection gives additional strength to the **376** model making your conveyor last longer! The **ALL-STEEL** construction provides unmatched structural integrity, whether the conveyor is extended, contracted or configured in simple or compound curves. Adjustable inner legs vary the height to achieve gravity flow. The fixed leg option gives added durability to application specific designs. The **NESTAFLEX 376** has a proven track record in the industry and is the choice for medium to high volume shipping and receiving departments. Call us today to learn more at 800.669.1501 or visit our website at www.flexmh.com.

CONVEYOR OPTIONS



376FL- Fixed Leg



Flexible Side Rails



Impact Conveyor



376AL- Adjustable Leg

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501



SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

| 18" WIDTHS | | 24" WIDTHS | | 30" WIDTHS | | LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS | | |
|------------|-----------------------|------------|-----------------------|------------|-----------------------|--|-------------------|-----------------------|
| Model 376 | Skate Wheels Per Axle | Model 376 | Skate Wheels Per Axle | Model 376 | Skate Wheels Per Axle | Contracted/Extended | Leg Sets Per Unit | Bed Sections Per Unit |
| 37618008 | 6 | 37624008 | 9 | 37630008 | 12 | 2' 7" - 8' 6" | 3 | 2 |
| 37618012 | 6 | 37624012 | 9 | 37630012 | 12 | 3' 7" - 12' 2" | 4 | 3 |
| 37618016 | 6 | 37624016 | 9 | 37630016 | 12 | 4' 8" - 15' 10" | 5 | 4 |
| 37618020 | 6 | 37624020 | 9 | 37630020 | 12 | 5' 8" - 19' 6" | 6 | 5 |
| 37618024 | 6 | 37624024 | 9 | 37630024 | 12 | 6' 8" - 23' 2" | 7 | 6 |
| 37618028 | 6 | 37624028 | 9 | 37630028 | 12 | 8' 2" - 28' 0" | 8 | 7 |
| 37618032 | 6 | 37624032 | 9 | 37630032 | 12 | 9' 2" - 31' 8" | 9 | 8 |
| 37618036 | 6 | 37624036 | 9 | 37630036 | 12 | 10' 3" - 35' 4" | 10 | 9 |
| 37618040 | 6 | 37624040 | 9 | 37630040 | 12 | 12' 1" - 41' 10" | 12 | 11 |
| 37618044 | 6 | 37624044 | 9 | 37630044 | 12 | 13' 1" - 45' 6" | 13 | 12 |
| 37618048 | 6 | 37624048 | 9 | 37630048 | 12 | 14' 4" - 49' 5" | 14 | 13 |
| 37618052 | 6 | 37624052 | 9 | 37630052 | 12 | 15' 4" - 53' 1" | 15 | 14 |
| 37618056 | 6 | 37624056 | 9 | 37630056 | 12 | 16' 5" - 56' 9" | 16 | 15 |
| 37618060 | 6 | 37624060 | 9 | 37630060 | 12 | 17' 5" - 60' 5" | 17 | 16 |

Also available in 36" widths.

NESTAFLEX 376 STANDARD FEATURES AND OPTIONS

NESTAFLEX
HEAVY DUTY CASTERS

376

SKATE WHEEL OPTIONS



N-Red Nylon



P-Black Polymer



S-Steel

CONVEYOR FORMATS

Available in 18", 24" and 30" widths. Lengths can be tailored to your specific application.

SKATE WHEEL OPTIONS

N-Red Nylon with nylon bushing for high-impact, short conveyors runs.

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

HEIGHT ADJUSTMENT

AL - Standard 28" - 36". Other height adjustments available.

FL - Fixed leg heights are available in a variety of configurations. Please contact your local representative for more information.

CONSTRUCTION

All steel construction.

LEGS

1 1/4" O.D., heavy duty square steel tubing with adjustable reinforced inner leg, double, welded cross braces are zinc plated. Four point bolted leg connection to the skate wheel axles and the 7 gauge steel side links.

HEAVY DUTY CASTERS

AL - Standard 5" x 1 1/2" casters with heavy duty stem. Casters with swivel/wheel steel lock pedal brakes are provided on the first and last legs. 6" x 2" and 8" x 2" casters are available for added strength and mobility.

FL - Standard 6" x 2" casters with the option for 5" or 8" casters depending on the application.

COUPLERS

Couplers are standard. Optional universal connectors available to connect to other types of conveyors.

BOX STOP/HANDLE

Standard retractable package stop serves also as an ergonomic handle.

AXLES

5/16" diameter steel axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

WARRANTY

24 month factory warranty.